



Digital Colour Printer

Superb print quality with a compact and lightweight body, the UP-D55 is ideal for use in a wide range of medical applications.

Just as medical image diagnostic equipment has changed in recent years – becoming smaller in size and progressing to digital technology – so too have the demands that customers place on their medical printers. In response to these changing demands, Sony introduces its new A5 digital colour printer, the UP-D55.

Using Sony dye sublimation technology, the UP-D55 produces A5-size prints of sharp and high quality at fast printing speeds. In addition, it has a compact and lightweight body so that it can fit into areas of limited space.

The optimum choice for many medical applications – for example in Endoscopy and Ultrasound systems – and also ideal for a wide range of scientific, industrial, and engineering uses, the UP-D55 provides you with working efficiency for high-performance printing.

Features

Superb Print Quality and Colour at Approximately 379 dpi Resolution

Incorporating Sony dye sublimation printing technology, the UP-D55 can provide photo-realistic quality prints with a high resolution of approx. 379 dpi and a total gradation of 8 bits each for yellow, magenta, and cyan. The innovative Photo Quality Processor image-processing system provides highly accurate image reproduction.

High-Speed Printing

The UP-D55 can output an A5-size print in approx. 20 seconds. This rapid printing speed is the result of the introduction of the Photo Quality Processor, combined with a highly sensitive print media.

Compact Size and Useful Front Operation

The UP-D55 has a compact design with dimensions of approx. 280 (W) x 125 (H) x 398 (D) mm (11 1/8 x 5 x 15 3/4 inches) and, thanks to the adoption of a new printing mechanism, a weight of only 9 kg (19 lb 13 oz). It is more compact than conventional models, enabling it to fit into limited space. Furthermore, it is designed with a convenient front panel that offers easy maintenance and flexible set up.



USB Interface

Equipped with a USB 2.0 interface as standard, the UP-D55 provides enhanced network flexibility. It supports Hi-Speed USB in addition to the existing Full-Speed USB.

Colour Balance Adjustment Function

A colour balance adjustment function allows you to easily select the colour that most closely matches your requirements. Three alternative gamma curves are also available, so you can select the one that provides the most suitable tonal range for your application.

2, 4 and 8 Split Image Print Mode

As well as printing out a single image, the UP-D55 can also provide two, four, and eight images split across a single sheet.

Medical Regulations

The UP-D55 complies with the following medical regulations that are applicable to medical devices:

- UL-60601-1, UL-60950,
- EN60601-1+EN60601-1-2 (EMC)

PC Compatibility

A PC utility driver software kit is bundled with the printer to enhance its flexibility. This software is compatible with Microsoft® Windows® 2000, XP.

Universal Powering System

The UP-D55 can operate with AC 100 V to 120 V and AC 220 V to 240 V power supplies - making it suitable for use all around the world.

Image Spool Function

The image spool function enables the second image data to be transferred from the computer at the same time as the first image is being printed out. This feature dramatically reduces the total printing time.

Resize Function

The resize function allows you to enlarge images for printing. Each VGA (640 x 480), SVGA (800 x 600) and XGA (1024 x 768) image can be set for automatic enlargement to match the size of the paper. Since you don't need to resize the image on your PC, the working efficiency is increased.

Useful Features

- The UP-D55 allows you to choose freely where the dialogue box that indicates printer messages will appear.
- The paper tray is equipped with a paper stopper that prevents printed sheets from sliding down.




Colour Printing Pack UPC-55


Contents: 200 sheets of print paper (100 sheets x 2 packs)
2 rolls of ink ribbon




Rear panel




Colour Balance Adjustment



2 Split Image



4 Split Image



8 Split Image

UP-D55 Specifications

Power requirements	100 to 120 V AC, 50/60 Hz (for 100 to 120 V AC users) 220 to 240 V AC, 50/60 Hz (for 220 to 240 V AC users)
Input current	Max. 2.8 A at 25 °C (for 100 to 120 V AC users) Max. 1.2 A at 25 °C (for 220 to 240 V AC users)
Operating temperature	5 °C to 35 °C (41 °F to 95 °F)
Operating humidity	20% to 80% (no condensation allowed)
Storage and transport temperature	-20 °C to 60 °C (-4 °F to 140 °F)
Storage and transport humidity	20% to 90% (no condensation allowed)
Dimensions	Approx. 280 (W) x 125 (H) x 398 (D) mm (11 1/8 x 5 x 15 3/4 inches)
Mass	Approx. 9 kg (19 lb 13 oz)
Printing system	Dye Sublimation Printing
Printable pixels	2528 x 1920 dots (when printing the full-image)
Printing area	169 (W) x 129 (H) mm (6 3/4 x 5 1/8 inches)
Total gradation	256 levels each for yellow, magenta, and cyan
Printing time	Approx. 20 seconds (when the printer is set to high speed)
Thermal head	379 dpi
Connectors	Hi-Speed USB (USB Rev 2.0) AC IN (for power input)
Supplied accessories	Paper tray (1) USB connecting cable (1) Ink ribbon holder (1) Software License Agreement (1) Before Using this Printer (1) CD-ROM (including the printer drivers and PDF files of multi-lingual instructions for use) (1)
Optional accessories	Colour Printing Pack Contents: 200 sheets of print paper (100 sheets x 2 packs) 2 rolls of ink ribbon

©2004 Sony Corporation. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. All non-metric weights and measures are approximate. Sony is a registered trademark of Sony Corporation. Microsoft and Windows are a registered trademarks of Microsoft Corporation. All other trademarks are the property of their respective owners.
CA UP-D55/GB-05/11/2004

SONY

SONY EUROPE

www.sonybiz.net